

CMOS Smart Camera

SM2-D1312 SERIES

1.4 Megapixel smart camera with programmable DSP


Features

- Photonfocus A1312 CMOS image sensor
- 1312 x 1082 pixel resolution
- Programmable Texas Instruments DSP
- HALCON Embedded compatible
- Exceptional SNR up to 300:1
- Dynamic range up to 120 dB via LinLog®
- Up to 108 fps @ full resolution
- JPEG compression @ 68 fps⁽¹⁾
- Global shutter
- Monochrome
- GigE interface
- 12 bit greyscale resolution

Compatible with



Spectral response of the Photonfocus A1312 CMOS image sensor



SM2-D1312-80-GB-12 VisionCam PS Type 2*	SM2-D1312-JPEG-100-GB-12 VisionCam PS Type 2*	SM2-D1312-160-GB-12 VisionCam PS Type 2*
--	--	---

Image sensor	
Image sensor	Photonfocus A1312 (3. Generation)
Technology	CMOS active pixel (APS)
Scanning system	Progressive scan
Optical format / diagonal	1" (13.6 mm diagonal) maximum resolution 2/3" (11.6 mm diagonal) 1024 x 1024 resolution
Resolution	1312 x 1082 pixels
Pixel size	8 µm x 8 µm
Active optical area	10.48 mm x 8.64 mm (maximum)
Dark current	0.65 fA/pixel
Full well capacity / SNR	~90 ke / 300:1
Spectral range	< 370 to 1000 nm (to 10 % of peak responsivity)
Responsivity	210 x 10 ³ DN / (J/m ²) @ 625 nm / 8 bit / gain = 1 (approximately 620 DN / (lux s) @ 625 nm / 8 bit / gain = 1)
Quantum Efficiency	> 50 %
Optical fill factor	> 60 %
Dynamic range	60 dB in linear mode; 120 dB with LinLog®
Colour format	Monochrome
Characteristic curve	Linear, LinLog®
Shutter mode	Global shutter
Read out mode	Sequential or simultaneous read out (read out during exposure only in linear mode) for higher frame rates

Camera			
Exposure time	10 µs ... 0.83 s / 50 ns steps	10 µs ... 0.67 s / 40 ns steps	10 µs ... 0.41 s / 25 ns steps
Frame rate	55 fps	68 fps	108 fps
Pixel clock	40 MHz	50 MHz	80 MHz
Camera taps	2 (internal)		
Greyscale resolution	8 bit / 10 bit / 12 bit		8 bit
Fixed pattern noise (FPN)	< 1 DN RMS @ 8 bit / gain = 1 / offset correction ON		
Analogue gain	1		
Digital gain	1 / 2 / 4 / 8		
Configuration interface	Built-in Webserver		
Trigger modes	<ul style="list-style-type: none"> • Free running (non triggered) • DSP controlled trigger • External trigger input 		
Features	<ul style="list-style-type: none"> • Region of Interest (ROI) • 512 Multiple ROI (MROI) • Decimation Y • Image correction • 2 Look-up tables (LUT) • Constant frame rate • Crosshair • Convolver 3x3 • Temperature • Image information • Realtime clock • JPEG Compression⁽¹⁾ • FTP Server • Extended trigger input and strobe output functionality Texas Instruments TMS320 C6415 @ 1GHz, 8000 MIPS / 256 MB SDRAM / 2 GB SD Card⁽²⁾ 		
CPU / RAM / Storage	GigE		
Interface	0°C ... +50°C		
Operating temperature	+12 V DC (±10 %)		
Power supply	10 W		
Power consumption	C-Mount (CS-Mount optional)		
Lens mount	60 x 60 x 137 mm ³		
Dimensions (H x W x L)	572 g		
Mass	CE / RoHS / WEEE		
Conformity	Adjustable backfocus; Opto-isolated I/Os; JTAG, RS232 Interface, RS422 Interface		
Specials			

Software	
Camera control	Built-in webserver
DSP Development tools	Texas Instruments Code Composer Studio 3.3, HALCON Embedded

* Product name used by Imago Technologies

⁽¹⁾ Feature only available for SM2-D1312-JPEG-100-GB-12 camera (for other cameras on request)

⁽²⁾ DSP TI TMS320 C6455 @ 1.2GHz, 9600 MIPS / 512 MB SDRAM (available on request)

All information provided in this flyer is believed to be accurate and reliable. No responsibility is assumed by Photonfocus AG for its use. Photonfocus AG reserves the right to make changes to this information without notice. Reproduction of this flyer in whole or in part, by any means, is prohibited without prior permission having been obtained from Photonfocus AG.

Version 1.1.10 | Nov 11